

(19) World Intellectual Property
Organization
International Bureau



557294

(43) International Publication Date
2 December 2004 (02.12.2004)

PCT

(10) International Publication Number
WO 2004/103810 A1

(51) International Patent Classification⁷: **B63H 11/08,**
B60F 3/00

(21) International Application Number:
PCT/GB2004/002135

(22) International Filing Date: 19 May 2004 (19.05.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0311495.6 19 May 2003 (19.05.2003) GB

(71) Applicant (for all designated States except US): **GIBBS TECHNOLOGIES LIMITED** [GB/GB]; Avenue Road, Nuneaton, Warwickshire CV11 4LY (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **GIBBS, Alan, Timothy** [GB/GB]; 28 Albert Bridge House, 127 Albert Bridge Road, London SW11 4PL (GB). **JENKINS, Neil, Graham** [GB/GB]; Mancetter Cottage, South Street, Atherton, Warwickshire CV9 1ED (GB).

(74) Agents: **PLUCKROSE, Anthony, William** et al.; Boulton Wade Tennant, Verulam Gardens, 70 Gray's Inn Road, London WC1X 8BT (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GR, GU, HE, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

GB, GD, GE, GH, GM, GR, GU, HE, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GR, GU, HE, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)
- of inventorship (Rule 4.17(iv)) for US only

[Continued on next page]

(54) Title: A JET DRIVE FOR AN AMPHIBIOUS VEHICLE



(57) Abstract: Amphibious vehicle (50), with reference to fig. 4, has jet drive (30) packaged behind power train (20, 22), but also configured to produce sufficient thrust for planing, despite drag created by open arches around retractable wheels (52). The ratio of thrust to jet intake length is at least 18kN/m. The ratio of fluid inlet area to fluid outlet area may be between (2.5) and (3.5). The rate of fluid flow through the jet may be 0 to 1.5 m³/sec. The maximum thrust may be 7700N, from an engine peak power of less than 135kW, with a jet less than 860mm long. The jet drive shaft may be skewed laterally; and may be cantilevered from a bearing in the conduit wall; which bearing may be rotated when the vehicle is driven on roads. Water flow through the jet may be reversible; alternatively, a reversing bucket may be fitted.

WO 2004/103810 A1



Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.